

mira

7 powerful adhesives ensure correct tile fixing every time



Easy-to-use
15 kg sacks with
carrying handle

mira's range of adhesives for fixing all types of tiles on floors and walls

① 3000 standardfix – grey

Tile adhesive for fixing of ceramic tiles on plaster and concrete surfaces. The mortar contains polymer additives and is applicable on stable substrates. It is not recommended for tiles with water absorption less than 3%.

② 3100 unifix – grey

Mainly for fixing ceramic tiles on untreated or primed, stable wall surfaces of plaster or lightweight concrete. Can also be used on walls treated with 4400 multicoat, painted surfaces, old tiles, etc. The tiling adhesive is for use on underlays subject to little or no deformation. Normally not recommended for tiles with less than 0.5% water absorption.

③ 3110 unifix – white

Same application range as 3100 unifix. Based on white cement and therefore ideal for fixing marble or thin translucent tiles, where grey tile adhesive would affect the colour.

3110 unifix is low-alkaline and thus neutralises alkaline stains in grouting, caused by moisture migration from the underlay.

④ 3130 superfix – white

Flexible adhesive based on white cement, used for fixing all kinds of natural stone and ceramic wall and floor tiles. It contains additives that neutralise alkaline stains in grouting, caused by moisture migration from the underlay.

The adhesive is able to absorb minor deformation stresses, which means that it is very suitable for underlays that are subjected to loads, e.g. thin heated floors, swimming pools, and for non-porous ceramic tiles with a water absorption of less than 0.5%. The adhesive will adhere to most underlays, but not direct on wooden panels, extensive concrete and lightweight concrete elements in new buildings, or where shrinkage is more than 0.4 ‰.



All adhesives are water and frost-proof and can be used both indoors and outdoors.

⑤ 3150 planfix – grey

Used for fixing all types of tiles on floors, the adhesive is particularly suitable for granite-ceramic and other non-absorbent tiles.

Special low-viscosity plastic additives ensure a consistent layer of adhesive under tiles. This in turn means fast and reliable fixing. Effective adhesion to non-porous, non-absorbent tiles. Specially recommended for shops, storerooms, and similar locations where the mechanical load on the floor is high. A 100% adhesive cover ensures that there are no cavities which can encourage bacteria in wet rooms and lead to frost cracks in outdoor applications.

For use on shrinkage and deformation-free concrete underlays and cement-plastered surfaces. Drying time about 3 hours.

⑥ 3230 superrapidfix – white

A quick-hardening version of 3130 superfix, suitable for use where tiling work has to be finished quickly. About 1 hour after it has been tiled, a floor will sustain light pedestrian traffic. This adhesive is therefore ideal for repairs and where time is important.

⑦ 3250 superplanfix – white

Used for fixing all types of ceramic tiles on floors. The adhesive is particularly suitable for granite-ceramic and other non-absorbent tiles.

A viscous and plastic-reinforced white tile adhesive which retains its elasticity and capability of withstanding heavy traffic while absorbing deformation stresses in the underlay. Neutralises concrete moisture from the underlay and alkaline stains from moisture migration.

Effective adhesion to non-porous, non-absorbent tiles and specially recommended for residential buildings, shops, storerooms, etc. where maximum adhesion, pressure distribution and elasticity is demanded from the adhesive layer. The 100% adhesive cover is a significant factor, especially where heavy loads occur. At the same time, it ensures that there are no cavities which can encourage bacteria in wet rooms and lead to frost cracks in outdoor applications. Suitable for all types of underlay such as concrete and cement-plastered surfaces, heated and unheated. Drying time about 3 hours.

mira

byggeprodukter a/s

EGEGÅRDSVEJ 2 • DK-4621 GADSTRUP • TEL. +45 46 19 19 46 • FAX +45 46 19 20 21

Distributor: